



SPK-IC6 Fireproof Ceiling Speakers



FEATURES

- Titanium Dome Tweeter
- Graphite Cone
- Sensitivity to 86 dB
- Taps for 8 Ohm, 70 and 100 volts
- Magnetic Speaker Grill
- Fire-Rated Back Box

DESCRIPTION

SPK-IC6 is a Fire Rated 40 watt In-Ceiling Speaker with a 1" titanium dome tweeter and a 6.5" Graphite cone driver with rubber surround. The SPK-IC6 includes taps for 8 ohm, 100-volt and 70-volt audio solutions and comes in a plenum fire rated back box. SPK-IC6 is perfect for K-12 classrooms, higher-ed classrooms and lecture halls, and medium to large meeting spaces.

Hall Technologies designs and builds complete solutions for AV applications. In order to provide our customers with a complete solution we have to offer all the components necessary to build out the application. Many of our solutions include built-in and external audio amplifiers. We offer a modest yet powerful line of speakers to compliment our audio solutions and add convenience to our customers for one stop shopping.



Feature	Detail
Tweeter	1" (25mm) Titanium dome
Woofers	6.5" (165 mm) Graphite Cone, Rubber Surround
Frequency Range+/-3	65 Hz -20KHZ
Power Handling RMS	80 W program , 40 W (IEEE 219)
Sensitivity	86 dB
Taps	8Ω,0,40W,20W,10W,5W
Impedance	8 ohms
Termination	Standard pressed connector
Included Accessories	Cut Out template grille
Dimensions(H*D)	9.01" x 10.11" (236 x 257mm)
Cut Out diameter	8.85" (225mm)
Certifications	CE
Attachment	Low-profile grille
Material	ABS+iron